



Model			TB 4	TB 6	TB 8	TB 9	TB 11	TB 12	TB 14	TB 15	TB 16	TB 18	TB 20	TB 22	TB 24
Dimensions															
Body length	A	m	3000	3450	3900	4350	4800	5400	6000	6000	6600	7200	7800	8400	9000
Body width	B	m	2200	2200	2350	2350	2500	2500	2500	2500	2500	2500	2500	2500	2500
Body height	C	m	1075	1150	1225	1225	1225	1225	1300	1375	1375	1375	1375	1375	1525
Loading height	D	m	2.13	2.26	2.36	2.36	2.59	2.59	2.67	2.79	2.79	2.84	2.89	3.04	3.04
		ft	7'0"	7'5"	7'9"	7'9"	8'6"	8'6"	8'9"	9'2"	9'2"	9'4"	9'6"	10'0"	10'0"
Overall length	E	m	4.63	5.08	5.54	5.99	6.45	7.06	7.67	7.67	8.28	8.89	9.50	10.11	10.72
		ft	15'2"	16'8"	18'2"	19'8"	21'2"	23'2"	25'2"	25'2"	27'2"	29'2"	31'2"	33'2"	35'2"
Overall width	F	m	2.16	2.16	2.31	2.31	2.46	2.46	2.46	2.46	2.46	2.46	2.46	2.46	2.46
		ft	7'1"	7'1"	7'7"	7'7"	8'1"	8'1"	8'1"	8'1"	8'1"	8'1"	8'1"	8'1"	8'1"
Tipped height	G	m	3.62	4.01	4.75	5.08	5.67	6.53	7.01	7.06	7.49	7.92	8.46	9.12	9.75
		ft	12'0"	13'2"	15'7"	16'8"	18'7"	21'5"	23'0"	23'2"	24'7"	26'0"	27'9"	29'11"	32'0"
Body capacity		m³	7.2	8.2	10.7	11.9	14.0	15.8	18.7	19.7	21.7	23.7	25.7	30.7	32.9
		ft³	253	290	377	420	496	558	659	697	767	837	907	1085	1162
Unladen weight		kg	1900	2000	2740	2910	3790	4250	4850	5060	5450	5850	6300	6800	7400
Misc.															
Hydraulic oil	L		15.5	15.5	15.5	24.6	24.6	33.5	33.5	33.5	33.5	40.0	40.0	42.0	42.0
		Gal.	3.4	3.4	3.4	5.3	5.3	7.2	7.2	7.2	7.2	7.2	8.6	8.6	9.2
Number of axles			1			2						3			
Axle beam	mm/studs		70/6			80/8		127 (COM)/10							
Brake size			300x60			350 x90		406x120			420x180		420 x220		420x180
Brake option			H						H/A						
Tyre size			11.5/80 x15.3		12.5/80x15.3		435/50 R19.5		385/65 R22.5				445/65 R22.5		
Bottom chassis			200x100 RHS			250x100 RHS			250x150 RHS			300x150 RHS			
Top chassis			150x75 RHS			150x75 RHS			150x100 RHS			200x100 RHS			